

PMC Casing Size

OD NOMINAL inch	OD		WEIGH lbs/ft	Wall		NOM. ID		DRIFT DIA		Coupling OD mm	Length mm	Make-up Loss mm	Pipe Section Sq.in
	inch	mm		inch	mm	inch	mm	inch	mm				
4 1/2	4.500	114.3	11.60	0.250	6.35	4.000	101.60	3.875	98.43	127.00	234.70	107.35	3.338
	4.500	114.3	13.50	0.291	7.39	3.918	99.52	3.795	96.39			107.35	3.848
	4.500	114.3	15.10	0.337	8.56	3.826	97.18	3.701	94.01			107.35	4.407
	4.500	114.3	16.90	0.380	9.65	3.740	95.00	3.615	91.82			107.35	4.918
	4.500	114.3	21.60	0.500	12.70	3.500	88.90	3.375	85.73			107.35	6.283
5	5.000	127.0	15.00	0.296	7.52	4.408	111.96	4.283	108.79	141.30	235.90	107.98	4.374
	5.000	127.0	18.00	0.362	9.19	4.276	108.61	4.151	105.44			107.98	5.275
	5.000	127.0	20.30	0.408	10.36	4.184	106.27	4.059	103.10			107.98	5.886
	5.000	127.0	23.20	0.478	12.14	4.044	102.72	3.919	99.54			107.98	6.791
	5.000	127.0	24.20	0.500	12.70	4.000	101.60	3.875	98.43			107.98	7.069
5 1/2	5.500	139.7	15.50	0.275	6.99	4.950	125.73	4.825	122.56	153.70	240.70	110.37	4.514
	5.500	139.7	17.00	0.304	7.72	4.892	124.26	4.767	121.08			110.37	4.962
	5.500	139.7	20.00	0.361	9.17	4.778	121.36	4.653	118.19			110.37	5.828
	5.500	139.7	23.00	0.415	10.54	4.670	118.62	4.545	115.44			110.37	6.630
	5.500	139.7	26.00	0.476	12.09	4.548	115.52	4.423	112.34			110.37	7.513
6 5/8	6.625	168.3	20.00	0.288	7.32	6.049	153.64	5.924	150.47	187.70	250.20	115.13	5.734
	6.625	168.3	24.00	0.352	8.94	5.921	150.39	5.796	147.22			115.13	6.937
	6.625	168.3	28.00	0.417	10.59	5.791	147.09	5.666	143.92			115.13	8.133
	6.625	168.3	32.00	0.475	12.07	5.675	144.15	5.550	140.97			115.13	9.177
	6.625	168.3	32.00	0.475	12.07	5.675	144.15	5.550	140.97			115.13	9.177
7	7.000	177.8	23.00	0.317	8.05	6.366	161.70	6.241	158.52	194.50	261.40	120.70	6.656
	7.000	177.8	26.00	0.362	9.19	6.276	159.41	6.151	156.24			120.70	7.549
	7.000	177.8	29.00	0.408	10.36	6.184	157.07	6.059	153.90			120.70	8.449
	7.000	177.8	32.00	0.453	11.51	6.094	154.79	5.969	151.61			120.70	9.317
	7.000	177.8	35.00	0.498	12.65	6.004	152.50	5.879	149.33			120.70	10.172
	7.000	177.8	38.00	0.540	13.72	5.920	150.37	5.795	147.19			120.70	10.959
	7.000	177.8	41.00	0.590	14.99	5.820	147.83	5.695	144.65			120.70	11.881
7 5/8	7.625	193.7	26.40	0.328	8.33	6.969	177.01	6.844	173.84	215.90	270.90	125.46	7.519
	7.625	193.7	29.70	0.375	9.53	6.875	174.63	6.750	171.45			125.46	8.541
	7.625	193.7	33.70	0.430	10.92	6.765	171.83	6.640	168.66			125.46	9.720
	7.625	193.7	39.00	0.500	12.70	6.625	168.28	6.500	165.10			125.46	11.192
	7.625	193.7	42.80	0.562	14.27	6.501	165.13	6.376	161.95			125.46	12.470
	7.625	193.7	45.30	0.595	15.11	6.435	163.45	6.310	160.27			125.46	13.141
	7.625	193.7	47.10	0.624	15.85	6.377	161.98	6.252	158.80			125.46	13.724
8 5/8	8.625	219.1	28.0	0.304	7.72	8.017	203.63	7.894	200.49	244.50	277.20	128.63	7.947
	8.625	219.1	32.0	0.352	8.94	7.921	201.19	7.798	198.06			128.63	9.149
	8.625	219.1	36.0	0.400	10.16	7.825	198.76	7.702	195.62			128.63	10.336
	8.625	219.1	40.0	0.450	11.43	7.725	196.22	7.602	193.08			128.63	11.557
	8.625	219.1	44.0	0.500	12.70	7.625	193.68	7.502	190.54			128.63	12.763
	8.625	219.1	49.0	0.557	14.15	7.511	190.78	7.388	187.64			128.63	14.118
	8.625	219.1	52.0	0.595	15.11	7.435	188.85	7.312	185.71			128.63	15.010
9 5/8	9.625	244.5	36.0	0.352	8.94	8.921	226.59	8.765	222.62	269.90	277.20	128.63	10.254
	9.625	244.5	40.0	0.395	10.03	8.835	224.41	8.679	220.44			128.63	11.454
	9.625	244.5	43.5	0.435	11.05	8.755	222.38	8.599	218.41			128.63	12.559
	9.625	244.5	47.0	0.472	11.99	8.681	220.50	8.525	216.53			128.63	13.572
	9.625	244.5	53.5	0.545	13.84	8.535	216.79	8.379	212.82			128.63	15.547
	9.625	244.5	58.4	0.595	15.11	8.435	214.25	8.279	210.28			128.63	16.879
	9.625	244.5	61.1	0.625	15.88	8.375	212.73	8.219	208.76			128.63	17.672
10 3/4	10.750	273.1	40.5	0.350	8.89	10.050	255.27	9.894	251.30	298.50	277.20	128.63	11.435
	10.750	273.1	45.5	0.400	10.16	9.950	252.73	9.794	248.76			128.63	13.006
	10.750	273.1	51.0	0.450	11.43	9.850	250.19	9.694	246.22			128.63	14.561
	10.750	273.1	55.5	0.495	12.57	9.760	247.90	9.604	243.94			128.63	15.947
	10.750	273.1	60.7	0.545	13.84	9.660	245.36	9.504	241.40			128.63	17.473
	10.750	273.1	65.7	0.595	15.11	9.560	242.82	9.404	238.86			128.63	18.982
11 3/4	11.750	298.5	47.0	0.375	9.53	11.000	279.40	10.844	275.43	323.80	277.20	128.63	13.401
	11.750	298.5	54.0	0.435	11.05	10.880	276.35	10.724	272.38			128.63	15.463
	11.750	298.5	60.0	0.489	12.42	10.772	273.61	10.616	269.64			128.63	17.300
	11.750	298.5	65.0	0.534	13.56	10.682	271.32	10.526	267.35			128.63	18.816
13 3/8	13.375	339.7	54.5	0.380	9.65	12.615	320.42	12.459	316.45	365.10	277.20	128.63	15.514
	13.375	339.7	61.0	0.430	10.92	12.515	317.88	12.359	313.91			128.63	17.487
	13.375	339.7	68.0	0.480	12.19	12.415	315.34	12.259	311.37			128.63	19.445
	13.375	339.7	72.0	0.514	13.06	12.347	313.61	12.191	309.65			128.63	20.768

Casing

Sizes and Grades

Outside Diameter	Nominal Weight	Outside Diameter D	Wall Thickness T		Type of End Finish					
					Grade					
					H-40	J-55 K-55	L-80 C-95	N-80	C-90 T-95	P-110
in	lb/ft	mm	in	mm						
4 1/2	9.50	114.3	0.205	5.21	S	S	-	-	-	-
	10.50	114.3	0.224	5.69	-	SB	-	-	-	-
	11.60	114.3	0.250	6.35	-	SLB	LB	LB	LB	LB
	13.50	114.3	0.290	7.37	-	-	LB	LB	LB	LB
5	11.50	127.0	0.220	5.59	-	S	-	-	-	-
	13.00	127.0	0.253	6.43	-	SLB	-	-	-	-
	15.00	127.0	0.296	7.52	-	SLB	LB	LB	LB	LB
	18.00	127.0	0.362	9.19	-	-	LB	LB	LB	LB
	21.40	127.0	0.437	11.10	-	-	LB	LB	LB	LB
	23.20	127.0	0.478	12.14	-	-	LB	LB	LB	LB
	24.10	127.0	0.500	12.70	-	-	LB	LB	LB	LB
5 1/2	14.00	139.7	0.244	6.20	S	S	-	-	-	-
	15.50	139.7	0.275	6.99	-	SLB	-	-	-	-
	17.00	139.7	0.304	7.72	-	SLB	LB	LB	LB	LB
	20.00	139.7	0.361	9.17	-	-	LB	LB	LB	LB
	23.00	139.7	0.415	10.54	-	-	LB	LB	LB	LB
6 5/8	20.00	168.3	0.288	7.32	S	SLB	-	-	-	-
	24.00	168.3	0.352	8.94	-	SLB	LB	LB	LB	LB
	28.00	168.3	0.417	10.59	-	-	LB	LB	LB	LB
	32.00	168.3	0.475	12.07	-	-	LB	LB	LB	LB
7	17.00	177.8	0.231	5.87	S	-	-	-	-	-
	20.00	177.8	0.272	6.91	S	S	-	-	-	-
	23.00	177.8	0.317	8.05	-	SLB	LB	LB	LB	-
	26.00	177.8	0.362	9.19	-	SLB	LB	LB	LB	LB
	29.00	177.8	0.408	10.36	-	-	LB	LB	LB	LB
	32.00	177.8	0.453	11.51	-	-	LB	LB	LB	LB
	35.00	177.8	0.498	12.65	-	-	LB	LB	LB	LB
	38.00	177.8	0.540	13.72	-	-	LB	LB	LB	LB
7 5/8	24.00	193.7	0.300	7.62	S	-	-	-	-	-
	26.40	193.7	0.328	8.33	-	SLB	LB	LB	LB	-
	29.70	193.7	0.375	9.53	-	-	LB	LB	LB	LB
	33.70	193.7	0.430	10.92	-	-	LB	LB	LB	LB
	39.00	193.7	0.500	12.70	-	-	LB	LB	LB	LB
	42.80	193.7	0.562	14.27	-	-	LB	LB	LB	LB
	45.30	193.7	0.595	15.11	-	-	LB	LB	LB	LB
	47.10	193.7	0.625	15.88	-	-	LB	LB	LB	LB

Sizes and Grades

Outside Diameter	Nominal Weight	Outside Diameter D	Wall Thickness T		Type of End Finish						
					Grade						
					H-40	J-55 K-55	L-80 C-95	N-80	C-90 T-95	P-110	
in	lb/ft	mm	in	mm							
8 5/8	24.00	219.1	0.264	6.71	-	S	-	-	-	-	-
	28.00	219.1	0.304	7.72	S	-	-	-	-	-	-
	32.00	219.1	0.352	8.94	S	SLB	-	-	-	-	-
	36.00	219.1	0.400	10.16	-	SLB	LB	LB	LB	LB	LB
	40.00	219.1	0.450	11.43	-	-	LB	LB	LB	LB	LB
	44.00	219.1	0.500	12.70	-	-	LB	LB	LB	LB	LB
	49.00	219.1	0.557	14.15	-	-	LB	LB	LB	LB	LB
9 5/8	32.30	244.5	0.312	7.92	S	-	-	-	-	-	-
	36.00	244.5	0.352	8.94	S	SLB	-	-	-	-	-
	40.00	244.5	0.395	10.03	-	SLB	LB	LB	LB	LB	LB
	43.50	244.5	0.435	11.05	-	-	LB	LB	LB	LB	LB
	47.00	244.5	0.472	11.99	-	-	LB	LB	LB	LB	LB
	53.50	244.5	0.545	13.84	-	-	LB	LB	LB	LB	LB
	58.40	244.5	0.595	15.11	-	-	LB	LB	LB	LB	LB
10 3/4	32.75	273.1	0.279	7.09	S	-	-	-	-	-	-
	40.50	273.1	0.350	8.89	S	SB	-	-	-	-	-
	45.50	273.1	0.400	10.16	-	SB	-	-	-	-	-
	51.00	273.1	0.450	11.43	-	SB	SB	SB	SB	SB	SB
	55.50	273.1	0.495	12.57	-	-	SB	SB	SB	SB	SB
	60.70	273.1	0.545	13.84	-	-	-	-	SB	SB	SB
	65.70	273.1	0.595	15.11	-	-	-	-	SB	SB	SB
11 3/4	42.00	298.5	0.333	8.46	S	-	-	-	-	-	-
	47.00	298.5	0.375	9.53	-	SB	-	-	-	-	-
	54.00	298.5	0.435	11.05	-	SB	-	-	-	-	-
	60.00	298.5	0.489	12.42	-	SB	SB	SB	SB	SB	SB
13 3/8	48.00	339.7	0.330	8.38	S	-	-	-	-	-	-
	54.50	339.7	0.380	9.65	-	SB	-	-	-	-	-
	61.00	339.7	0.430	10.92	-	SB	-	-	-	-	-
	68.00	339.7	0.480	12.19	-	SB	SB	SB	SB	SB	SB
	72.00	339.7	0.514	13.06	-	-	SB	SB	SB	SB	SB
16	65.00	406.4	0.375	9.53	S	-	-	-	-	-	-
	75.00	406.4	0.438	11.13	-	SB	-	-	-	-	-
	84.00	406.4	0.495	12.57	-	SB	-	-	-	-	-
18 5/8	87.50	473.1	0.435	11.05	S	SB	-	-	-	-	-
20	94.00	508.0	0.438	11.13	SL	SLB	-	-	-	-	-
	106.50	508.0	0.500	12.70	-	SLB	-	-	-	-	-
	133.00	508.0	0.635	16.13	-	SLB	-	-	-	-	-

S = Short Round Thread L = Long Round Thread B = Buttress Thread